

2SD1273, 2SD1273A

Silicon NPN triple diffusion planar type


For power amplification with high forward current transfer ratio
Complementary to 2SB1299

■ Features

- High forward current transfer ratio h_{FE}
- Satisfactory linearity of forward current transfer ratio h_{FE}
- Full-pack package which can be installed to the heat sink with one screw

■ Absolute Maximum Ratings ($T_C=25^\circ\text{C}$)

Parameter	Symbol	Ratings	Unit
Collector to base voltage	V_{CBO}	80	V
2SD1273			
2SD1273A		100	
Collector to emitter voltage	V_{CEO}	60	V
2SD1273			
2SD1273A		80	
Emitter to base voltage	V_{EBO}	6	V
Peak collector current	I_{CP}	6	A
Collector current	I_C	3	A
Base current	I_B	1	A
Collector power dissipation	P_C	40	W
$T_C=25^\circ\text{C}$			
$T_a=25^\circ\text{C}$		2	
Junction temperature	T_j	150	$^\circ\text{C}$
Storage temperature	T_{stg}	-55 to +150	$^\circ\text{C}$



■ Electrical Characteristics ($T_C=25^\circ\text{C}$)

Parameter	Symbol	Conditions	min	typ	max	Unit
Collector cutoff current	I_{CBO}	$V_{CB} = 80V, I_E = 0$			100	μA
2SD1273A		$V_{CB} = 100V, I_E = 0$			100	
Collector cutoff current	I_{CEO}	$V_{CE} = 40V, I_B = 0$			100	μA
Emitter cutoff current	I_{EBO}	$V_{CB} = 6V, I_C = 0$			100	μA
Collector to emitter voltage	V_{CEO}	$I_C = 25\text{mA}, I_B = 0$	60			V
2SD1273A			80			
Forward current transfer ratio	h_{FE}^*	$V_{CE} = 4V, I_C = 0.5A$	500		2500	
Collector to emitter saturation voltage	$V_{CE(sat)}$	$I_C = 2A, I_B = 0.05A$			1	V
Transition frequency	f_T	$V_{CE} = 12V, I_C = 0.2A, f = 10\text{MHz}$		50		MHz

* h_{FE} Rank classification

Rank	Q	P	O
h_{FE}	500 to 1000	800 to 1500	1200 to 2500

Note: Ordering can be made by the common rank (PQ rank $h_{FE} = 500$ to 1500) in the rank classification.

