


GENERAL PURPOSE APPLICATION,
SWITCHING APPLICATION.

FEATURES

- Excellent h_{FE} Linearity.
- Complementary to KTC9012

MAXIMUM RATINGS (Ta=25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	V_{CB0}	40	V
Collector-Emitter Voltage	V_{CE0}	30	V
Emitter-Base Voltage	V_{EB0}	5	V
Collector Current	I_C	500	mA
Emitter Current	I_E	500	mA
Collector Power Dissipation	P_C	625	mW
Junction Temperature	T_J	150	°C
Storage Temperature Range	T_{STG}	-55~150	°C



ELECTRICAL CHARACTERISTICS (Ta=25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYPE	MAX.	UNIT
Collector Cut-off Current	I_{C0}	$V_{CE}=35V, I_E=0$	-	-	0.1	μA
Emitter Cut-off Current	I_{E0}	$V_{BE}=5V, I_C=0$	-	-	0.1	μA
DC Current Gain	$h_{FE}(Nte)$	$V_{CE}=1V, I_C=50mA$	64	-	240	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=100mA, I_E=10mA$	-	0.1	0.25	V
Base-Emitter Voltage	V_{BE}	$I_C=100mA, V_{CE}=1V$	-	0.8	1.0	V
Transition Frequency	f_T	$V_{CE}=6V, I_C=20mA, f=100MHz$	140	-	-	MHz
Collector Output Capacitance	C_{ob}	$V_{CE}=6V, I_C=0, f=1MHz$	-	7.0	-	pF

Note : h_{FE} Classification D:84~91, E:78~112, F:96~135, G:118~160, H:144~202, I:176~246