


GENERAL PURPOSE APPLICATION,
SWITCHING APPLICATION.

FEATURES

- Excellent h_{FE} Linearity
: $h_{FE}(I_c=0.1mA)/h_{FE}(I_c=2mA)=0.95(Typ.)$
- Low Noise (NF=1dB(Typ.) at $f=1kHz$)
- Complementary to KTC9014.

MAXIMUM RATINGS (Ta=25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	V_{CB}	-50	V
Collector-Emitter Voltage	V_{CE}	50	V
Emitter-Base Voltage	V_{EB}	-5	V
Collector Current	I_c	-150	mA
Emitter Current	I_E	150	mA
Collector Power Dissipation	P_c	625	mW
Junction Temperature	T_j	150	°C
Storage Temperature Range	T_{stg}	-55~150	°C



ELECTRICAL CHARACTERISTICS (Ta=25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current	I_{CBO}	$V_{CE}=-50V, I_E=0$	-	-	-50	nA
Emitter Cut-off Current	I_{EBO}	$V_{EB}=-5V, I_C=0$	-	-	-100	nA
DC Current Gain	h_{FE} (Note)	$V_{CE}=-5V, I_C=1mA$	60		600	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=-100mA, I_E=-10mA$	-	-0.1	-0.3	V
Transition Frequency	f_T	$V_{CE}=-10V, I_C=1mA, f=100MHz$	60	-	-	MHz
Collector Output Capacitance	C_{ce}	$V_{CE}=-10V, I_C=0, f=1MHz$	-	4.0	7.0	pF
Noise Figure	NF	$V_{CE}=-5V, I_C=0.1mA, R_g=10k\Omega, f=1kHz$	-	1.0	10	dB

Note : h_{FE} Classification A:50~150 , B:100~300 , C:200~600