


HEXFET[®] Power MOSFET

- Dynamic dv/dt Rating
- Repetitive Avalanche Rated
- P-Channel
- Isolated Central Mounting Hole
- Fast Switching
- Ease of Paralleling
- Simple Drive Requirements



$$V_{DS} = -200V$$


$$R_{DS(on)} = 0.50\Omega$$

$$I_D = -12A$$

Description

Third Generation HEXFETs from International Rectifier provide the designer with the best combination of fast switching, ruggedized device design, low on-resistance and cost-effectiveness.

The TO-247 package is preferred for commercial industrial applications where higher power levels preclude the use of TO-220 devices. The TO-247 is similar but superior to the earlier TO-218 package because of its isolated mounting hole. It also provides greater creepage distance between pins to meet the requirements of most safety specifications.



TO-247AC

DATA
SHEETS

Absolute Maximum Ratings

Parameter	Max.	Units
I_D @ $T_J = 25^\circ C$ Continuous Drain Current, $V_{GS} @ -10V$	-12	A
I_D @ $T_J = 100^\circ C$ Continuous Drain Current, $V_{GS} @ -10V$	-7.5	
I_{DM} Pulsed Drain Current (10)	-48	
P_D @ $T_J = 25^\circ C$ Power Dissipation	150	W
Linear Derating Factor	1.2	W/ $^\circ C$
V_{GS} Gate-to-Source Voltage	+20	V
E_{AS} Single Pulse Avalanche Energy (1)	780	mJ
I_{AS} Avalanche Current (1)	-12	A
E_{AR} Repetitive Avalanche Energy (1)	15	mJ
dv/dt Peak Diode Recovery dv/dt (2)	-5.0	V/ns
T_J Operating Junction and Storage Temperature Range	-55 to +150	$^\circ C$
Soldering Temperature, for 10 seconds	300 (1.6mm from case)	
Mounting Torque, 6-32 or M3 screw	10 lb/in (1.1 N-m)	

Thermal Resistance

Parameter	Min.	Typ.	Max.	Units
R_{JC} Junction-to-Case	—	—	0.83	$^\circ C/W$
R_{CS} Case-to-Sink, Flat, Gaseous Surface	—	0.24	—	
R_{JA} Junction-to-Ambient	—	—	40	

Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Test Conditions
V_{BRSS}	Drain-to-Source Breakdown Voltage	-200	—	—	V	$V_{GS}=0\text{V}$, $I_S=-200\mu\text{A}$
$\Delta V_{BRSS}/\Delta T_J$	Breakdown Voltage Temp. Coefficient	—	-0.20	—	mV/°C	Reference to 25°C , $I_S=-1\text{mA}$
$R_{DS(on)}$	Static Drain-to-Source On-Resistance	—	0.50	—	Ω	$V_{GS}=10\text{V}$, $I_D=-7.2\text{A}$ ①
$V_{GS(th)}$	Gate Threshold Voltage	2.0	—	4.0	V	$V_{DS}=V_{GS}$, $I_D=-250\mu\text{A}$
g_m	Forward Transconductance	4.2	—	—	S	$V_{DS}=-50\text{V}$, $I_D=-7.2\text{A}$ ②
I_{SSS}	Drain-to-Source Leakage Current	—	—	100	μA	$V_{GS}=200\text{V}$, $V_{DS}=0\text{V}$
		—	—	-500	μA	$V_{GS}=-180\text{V}$, $V_{DS}=0\text{V}$, $T_J=125^\circ\text{C}$
I_{GSS}	Gate-to-Source Forward Leakage	—	—	100	nA	$V_{DS}=20\text{V}$
	Gate-to-Source Reverse Leakage	—	—	100	nA	$V_{DS}=20\text{V}$
Q_g	Total Gate Charge	—	44	—	nC	$I_D=-11\text{A}$
Q_{GS}	Gate-to-Source Charge	—	—	7.1	nC	$V_{DS}=-180\text{V}$
Q_{GD}	Gate-to-Drain ("Miller") Charge	—	—	27	nC	$V_{GS}=10\text{V}$ See Fig. 9 and 13 ③
t_{ON}	Turn-On Delay Time	—	14	—	ns	$V_{DS}=100\text{V}$
t_R	Rise Time	—	43	—	ns	$I_D=-11\text{A}$
t_{OFF}	Turn-Off Delay Time	—	30	—	ns	$R_G=9.1\Omega$
t_F	Fall Time	—	30	—	ns	$R_G=3.8\Omega$ See Figure 10 ③
L_i	Internal Drain Inductance	—	5.0	—	nH	Between lead, 5 mm (0.236 in.) from package and central die contact
L_s	Internal Source Inductance	—	10	—	nH	
C_{iss}	Input Capacitance	—	200	—	pF	$V_{DS}=0\text{V}$
C_{oss}	Output Capacitance	—	570	—	pF	$V_{GS}=25\text{V}$
C_{rfs}	Reverse Transfer Capacitance	—	01	—	pF	$f=1.0\text{MHz}$ See Figure 5



Source-Drain Ratings and Characteristics

	Parameter	Min.	Typ.	Max.	Units	Test Conditions
I_S	Continuous Source Current (Body Diode)	—	—	-12	A	MOSFET symbol showing the diode in reverse
I_{SM}	Pulsed Source Current (Body Diode) ④	—	—	-18	A	p-n junction code
V_{SD}	Diode Forward Voltage	—	—	-5.0	V	$T_J=25^\circ\text{C}$, $I_S=-1\text{A}$, $V_{GS}=0\text{V}$ ⑤
t_{rr}	Reverse Recovery Time	—	250	300	ns	$T_J=25^\circ\text{C}$, $I_S=-11\text{A}$
Q_{rr}	Reverse Recovery Charge	—	2.9	3.5	μC	$I_{ASR}=100\text{A}/\mu\text{s}$ ⑥
t_{on}	Forward Turn-On Time	Intrinsic turn-on time is negligible (turn-on is dominated by L_i and L_s)				

Notes:

① Repetitive rating; pulse width limited by max. J_c and temperature (See Figure 11)

② $I_{DS}=-12\text{A}$, $dI_{DS}/dt=150\text{A}/\mu\text{s}$, $V_{DS}=V_{BRSS}$, $T_J=25^\circ\text{C}$

③ $V_{DS}=50\text{V}$, starting $T_J=25^\circ\text{C}$, $L=8.2\text{nH}$, $R_G=25\Omega$, $I_{DS}=-12\text{A}$ (See Figure 12)

④ Pulse width $\leq 300\mu\text{s}$; duty cycle $\leq 2\%$.




Fig 1. Typical Output Characteristics,
 $T_C=25^{\circ}\text{C}$




Fig 2. Typical Output Characteristics,
 $T_C=150^{\circ}\text{C}$




Fig 3. Typical Transfer Characteristics




Fig 4. Normalized On-Resistance
Vs. Temperature




Fig 9. Maximum Drain Current Vs. Case Temperature




Fig 10a. Switching Time Test Circuit




Fig 10b. Switching Time Waveforms




Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Case




Fig 12a. Unclamped Inductive Test Circuit




Fig 12b. Unclamped Inductive Waveforms




Fig 13a. Basic Gate Charge Waveform




Fig 12c. Maximum Avalanche Energy Vs. Drain Current




Fig 13b. Gate Charge Test Circuit

Appendix A: Figure 14, Peak Diode Recovery dv/dt Test Circuit – See page 1506

Appendix B: Package Outline Mechanical Drawing – See page 1511

Appendix C: Part Marking Information – See page 1517

International
ICR Rectifier